



Tel : + 27 11 886-7874 Fax : + 27 11 787-0178
Email : sales@sinetech.co.za

Dear Customer

General :

Before you purchase a Home/Farm/Small Business backup system you should consider the following facts. Backup systems and batteries are very expensive and every appliance that you choose to run on the backup system which is not absolutely necessary, can increase the cost of the backup system drastically. We therefore recommend that you carefully consider which appliances should run on the backup system after a power failure.

Things to consider :

Before we can size the correct backup system you must consider the following :

1. Which items are absolutely necessary to be run on the backup system after power failure.
2. Write down the power requirements of each appliance / item in watts, VA or amps. These values are normally found on the production labels on the appliance or in the appliance manual.
3. Calculate the total wattage of all items which will be run on the backup system.
4. Consider what the most applicable backup time will be for your area. In other words how long are the power failures you experience normally.

Catalogue explanation :

The product catalogue indicates, in picture format, what type of backup systems are available. When ordering you can refer to the model no. for each individual system (26 systems in total). The recharge time shown assumes that the battery set is run down completely until the inverter system has switched off. This recharge times are calculated and can vary depending on age of the battery, recharge state of the battery and environmental temperatures, etc.

The backup times indicated in the catalogue are purely examples and relate to the power indicated. Each user should experiment to see how long the backup time will be in their own particular case - as long as the total wattage does not exceed the maximum allowable wattage of the inverter as indicated. It is recommended that you run the inverter not more than 80% loaded to allow for some inrush current capability.

Note that the backup times in the catalogue are related to specific load examples. For example Item 1. Model PM-A-0600CA-112A can produce a backup time of 9 hours with a load of 100 watts but if you use the inverter to its maximum allowable wattage of 550W, the backup time will only be about 45 minutes. This same principle applies to all the systems. In the pricelist the backup times are calculated at full load and at half load of the maximum capability of the inverter.

All of these systems have an automatic switchover facility so that they switch on automatically when the power fails. When power returns, the unit will automatically switch back to battery recharge mode and you appliances will run on standard mains again.

At a first glance some of the systems look the same but there are quite substantial differences. Some of the units have either larger inverters or larger battery chargers or larger battery banks. The catalogue is divided into 2 sections: the first section displays only smaller systems which use modified sine-wave inverters; the second section displays larger systems which use pure sine-wave inverters.

The difference between modified and pure sine-wave inverters is explained below. Please read this before making any decisions.

Modified Sine-wave Inverters:

This type of inverter is the most cost effective one but has also many drawbacks.

The Modified Sine-Wave inverter or also called Quasi - Sine Wave Inverter has some limitations. These types of inverters produce a negative by-product which is electrical noise. It is a fact that many TV's and stereos are incapable of eliminating common mode noise. As a result, powering such equipment with a Modified Sine Wave Inverter may cause a "grain" or small amount of "snow" or horizontal stripes on your TV picture, or a "hum" on your sound system. These are some of the appliances that may experience problems when running off Modified Sine-Wave inverters:

- Laser printers, photocopiers, magneto-optical hard drives
- Some fluorescent lights with standard inductive ballasts
- Power tools employing "solid state" power or variable speed control
- Some battery chargers for cordless tools
- Sometimes produces interference in some television sets
- Digital clocks with radios
- Can produce interference to some Computers
- Ceilings Fans or standard Fans
- Sewing machines with speed/microprocessor control
- Medical equipment such as oxygen concentrators
- Any load, which has high inductive and/or capacitive components, e.g. any motor, water pumps.
- Are normally not electronically protected (Only by standard fuse)
- Modified sine-wave inverters are usually only protected by standard fuses which, under normal circumstances, are not always fast enough, therefore they are by far more vulnerable to failure and definitely get damaged if you make a mistake.

Modified Sine-wave Inverters with built in Battery Charger and Changeover switch:

Same as above but with a 6 – 25 Amp built in battery charger. Some models have also a changeover switch added. This will allow you to use this model as "Standby System" and will function as follows.

While the mains or Eskom is present, the battery charger will recharge the battery and will keep the battery on float charge until the power fails. The change over switch will immediately switch over to the inverter and any load connected to the inverter will carry on running until the battery is exhausted. After power is restored the unit will switch automatically back to Eskom power and will start to recharge the battery bank as quick as possible.

Pure Sine-wave Inverters:

This type of Sine-wave inverter is the most technically advanced and reliable model and has basically no drawbacks with the exception that it costs twice the price. With his "perfect" sine wave output, the power produced by the inverter fully assures that your sensitive loads will be

correctly powered, with no interference. Basically any load can be connected to this inverter without any problems. The better quality sine wave inverters will provide excellent regulation and very importantly, a very high inrush current capability which is very important to start heavy capacitive or inductive loads like motors and deep freezers.

This is the best output waveform you can get out of an inverter and all appliances are able to run off it without interference or overheating. Some of its advantages are as follows:

- Output voltage waveform is pure sine wave with very low harmonic distortion and the same or better than the Eskom supply
- Inductive loads like microwave ovens and motors run correctly, quieter and cooler
- Reduces audible and electrical noise in fans, fluorescent lights, audio amplifiers, TV, game consoles, computers, fax, and answering machines
- Prevents crashes in computers, unreadable print outs, and glitches and noise in monitors
- It can be efficiently electronically protected in overload, overvoltage, undervoltage and over temperature conditions

Pure Sine-wave Inverters with built in Battery Charger and Changeover switch:

Same as above but with a 6 – 100 Amp built in battery charger. Some models have also a changeover switch added. This will allow you to use this model as “Standby System” and will function as follows.

While the mains or Eskom is present, the battery charger will recharge the battery and will keep the battery on float charge until the power fails. The change over switch will immediately switch over to the inverter and any load connected to the inverter will carry on running until the battery is exhausted.

It is highly recommended, wherever possible, that a Pure Sine-Wave Inverter is used. This will pre-empt possible operating problems at a later stage.

Pricelist explanation :

After choosing the right inverter for your application you should then refer to the model nos. for ordering. The first price column shows the price for the inverter with built-in battery charger only. The second price column shows the price for the inverter/battery charger and includes the battery set and battery cable set. Prices for battery stands or battery cabinets are shown under the section ‘Accessories’ and these have to be ordered separately.

Installation :

All of the systems offered can be used either as totally independent free standing backup systems or can be hard wired into your electrical system (by a qualified electrician). Great care has to be taken if the system is hard wired as if it is incorrectly installed the system could be damaged. Sinetech does not take any responsibility for incorrectly installed systems or any consequential damage which may be caused as a result thereof.

Sinetech

Tel : + 27 11 886 7874 Fax : + 27 11 787-0178 Email : sales@sinetech.co.za www.sinetech.co.za