



Dimension drawing DV M TT 2P 255 (FM)

Basic circuit diagram DV M TT 2P 255 FM

DV M TT 2P 255 (FM): Modular combined lightning current and surge arrester for single-phase TT and TN systems ("1+1" circuit)

- **Prewired combined spark-gap-based lightning current and surge arrester, consisting of a base part and plug-in protection modules**
- **Maximum system availability due to RADAX Flow follow current limitation**
- **No tripping of 20 A gL/gG fuses up to 50 kA_{rms} short-circuit currents**
- **Lightning current discharge capacity: 50 kA (10/350 μs)**
- **Allows for protection of terminal equipment**
- **Fault indication by red mark in the inspection window**
- **Easy exchange of protection modules by module locking system with releasing button**
- **Tested for vibration- and shock-proofness acc. to EN 60068-2**

DV M TT 2P 255

SPD according to EN 61643-11	Type 1
SPD according to IEC 61643-1	Class I
Nominal ac voltage [U _N]	230 V
Max. continuous ac voltage [U _C]	255 V
Lightning impulse current (10/350 μs) [L+N-PE]	50 kA
Lightning impulse current (10/350 μs) [L-N] [I _{imp}]	25 kA
Lightning impulse current (10/350 μs) [N-PE] [I _{imp}]	50 kA
Nominal discharge current (8/20 μs) [I _n]	25 / 50 kA
Voltage protection level [L-N] [U _{p1}]	≤ 1.5 kV
Voltage protection level [N-PE] [U _{p1}]	≤ 1.5 kV
Follow current extinguishing capability [L-N] ac [I _{ff}]	50 kA _{rms}
Follow current extinguishing capability [N-PE] ac [I _{ff}]	100 A _{rms}
Follow current limitation/Selectivity	no tripping of a 32 A gL/gG fuse up to 50 kA _{rms} (prosp.)
Response time [t _A]	≤ 100 ns
Max. backup fuse (L) up to I _K = 50 kA _{rms}	315 A gL/gG
Max. backup fuse (L) at I _K > 50 kA _{rms}	200 A gL/gG
Max. backup fuse (L-L')	125 A gL/gG
TOV voltage [L-N] [U _{T1}]	440 V / 5 sec.
TOV voltage [N-PE] [U _{T1}]	1200 V / 200 ms
Operating temperature range (parallel connection) [T _{UP}]	-40°C...+80°C
Operating temperature range (series connection) [T _{US}]	-40°C...+60°C
Operating state/fault indication	green / red
Cross-sectional area (L, L', N, N', PE, ⚡) [min.]	10 mm ² solid/flexible
Cross-sectional area (L, N, PE) [max.]	50 mm ² stranded/35 mm ² flexible

Cross-sectional area (L', N', $\frac{1}{2}$) [max.]	35 mm ² stranded/25 mm ² flexible
Mounting on	35 mm DIN rail acc. to EN 60715
Enclosure material	red thermoplastic, UL 94-V-0
Degree of protection	IP 20
Dimension	4 mods., DIN 4
Approvals, Certifications	KEMA, VDE
Ordering information	
Type	DV M TT 2P 255
Part No.	951 110
Packing unit	1 pcs.

Change in form and technology, with masses, weights and materials we reserve ourselves in the sense of the progress of the technology. The illustrations are noncommittal.

For more information contact :

SINETECH

Tel : + 27 11 886 7874

Fax : +27 11 787 0178

Email : sales@sinetech.co.za

343 Kent Avenue, Ferndale, Randburg, Johannesburg, South Africa