

Maintenance Free

DELTEC / DELCO / DELPHI

Deltec Freedom batteries never need water. Antimony-free plates cut electrolyte loss from gassing. Special liquid-gas separator keeps electrolyte inside.

No filler caps - so no electrolyte contamination, over watering or damage in use. Unique wrought lead-calcium grid design means less internal corrosion and efficient current conductivity for more power and longer life. It also cuts gassing, resists overcharge, heat and thermal runaway. Generous electrolyte reserve, factory checked for purity and specific gravity, is sealed in to last the service life of the battery.

"Spin-formed", cold-forged terminals for high torque strength. Double-sealed for leak protection. Terminal types :

- Standard tapered posts with either right-hand or left-hand positive
- Special lug terminals



Applications :

- UPS Systems
- DC Standby Systems
- Marine
- Communications
- Solar Applications

TECHNICAL SPECIFICATIONS

| Model | Volts | Capacity at 20 Hr Rate (Ah) | Cold Cranking Amps BCI Spec 0 deg F (-18 deg C) Amps | Reserve Capacity Minutes | Length | Width | Height | Mass Kg | Terminal |
|---------------|-------|-----------------------------|--|--------------------------|--------|-------|--------|---------|----------|
| 2535 Slimline | 12 | 35 | 330 | 52 | 196 | 128 | 219 | 10.2 | Round |
| 2736 | 12 | 36 | 325 | 60 | 207 | 175 | 175 | 11.5 | Round |
| 4736 | 12 | 36 | 400 | 75 | 207 | 175 | 175 | 12.1 | Flat Lug |
| 3545 Slimline | 12 | 45 | 450 | 75 | 237 | 128 | 219 | 12.4 | Round |
| 2745 | 12 | 45 | 400 | 75 | 207 | 175 | 175 | 12.1 | Round |
| 4745 | 12 | 45 | 400 | 75 | 207 | 175 | 175 | 12.1 | Flat Lug |
| 2766 | 12 | 66 | 550 | 110 | 277 | 175 | 175 | 16.4 | Round |
| 1250 | 12 | 102 | 625 | 180 | 330 | 175 | 240 | 26 | Stud |
| 1251 | 12 | 102 | 625 | 180 | 330 | 175 | 240 | 26 | Round |

We reserve the right to change specifications without prior notice

Cat/DELTEK

Tel: (011) 886-787

Fax: (011) 787-0178

Email: sales@sinetech.co.za