

Eaton Evolution S

1250/1750/2500/3000 VA



Eaton Evolution S



Eaton Evolution S with EXB

Advanced protection for:

- Rack servers
- Tower servers
- Network devices
- Storage systems



Line interactive

High density protection for network devices

Maximum availability

- **Powershare:** the Eaton Evolution S output sockets are individually controlled to provide load-shedding to maximise the backup time and provide remote reboot and sequential start-up as standard
- **Continuous power supply:** Hot swappable batteries. The optional HotSwap MBP (Maintenance By-Pass) module allows the UPS to be replaced without interrupting the power supply
- **Long backup times:** 1 to 4 EXB battery units can be added to the Evolution S
- **Pure sinewave output:** when operating in batterie mode the Eaton Evolution still provides high quality output signal for sensitive connected equipment

Minimum total cost of ownership

- **Line-interactive HF technology:** the best price/performance ratio
- **No additional cost:** all models are provided with tower stands and rail kits
- **Remote supervision:** a wide range of options using the Eaton Software suite, including point-to-point power management, SNMP, relay outputs, etc...

Totally flexibility

Evolution has unmatched Flexibility.

- **Format:** Evolution S is available in RT2U convertible rack/tower version (optimised for rack mounting) or RT3U (for tower or short-depth racks)
- **Connections:** with FlexPDU and HotSwap MBP the Evolution S can be connected by sockets or terminal blocks. They can be installed as required behind, on the side or on top of the unit
- **Compatible with high power factor loads:** the Evolution S are rated for 0.9 total power factor (1250 VA/1150 W, 1750 VA/1600 W, 2500 VA/2250 W and 3000 VA/2700 W)
- **Communication:** the Evolution S includes both serial and USB ports, plus remote On/Off connector and an extra slot for optional communication cards. The UPS comes with a complete Eaton software suite.

EATON

Powering Business Worldwide

Eaton Evolution S UPS

1250/1750/2500/3000 VA

- 1 Full user interface:
 - ON/OFF button for UPS and outlets
 - Load protected/ not protected LED
 - Utilised power level/Battery charge level
 - Status of switchable outlets
- 2 Panel for batteries replacement (Hotswappable)
- 3 1 USB port + 1 serial port + remote ON/OFF



- 4 EXB battery unit connector
- 5 EXB units recognised automatically
- 6 8 IEC 10A sockets, including 4 programmable sockets
- 7 Communication card slot

Eaton Evolution S 3000 RT2U Netpack

Technical Specifications

	1250	1750	2500	3000	
Rating (VA/W)	1250 VA / 1150 W	1750 VA / 1600 W	2500 VA / 2250 W	3000 VA / 2700 W	
Format	RT2U (tower / rack 2U)	RT2U (tower / rack 2U)	RT2U (tower / rack 2U)	RT2U & RT3U	
Electrical characteristics					
Technology	Line-Interactive High Frequency (Booster + Fader)				
Input voltage and frequency ranges without using batteries	160V-294V (adjustable to 150V-294V) 47 to 70 Hz (50 Hz system), 56.5 to 70 Hz (60 Hz system), up to 40 Hz in low-sensitivity mode (programmable using Personal Solution-Pac software).				
Output voltage and frequency	230 V (+6/-10 %) (Adjustable to 200 V (10 % derating of output power) / 208 V / 220 V / 230 V / 240 V), 50/60 Hz +/- 0.1 %				
Connections					
Input	1 IEC C14 (10 A) socket	1 IEC C14 (10 A) socket	1 IEC C20 (16 A) socket	1 IEC C20 (16 A) socket	
Outputs	8 IEC C13 (10 A)	8 IEC C13 (10 A)	8 IEC C13 (10 A) sockets 1 IEC C19 (16 A) socket	8 IEC C13 (10 A) sockets 1 IEC C19 (16 A) socket	
Remotely controlled sockets	2 groups of 2 x IEC C13 (10 A)				
Additional outputs with HS MBP	4 FR/Schuko sockets or 3 BS sockets or 6 IEC 10 A sockets or terminal blocks (HW version)				
Additional outputs with FlexPDU	8 FR/Schuko sockets or 6 BS sockets or 12 IEC 10 A sockets				
Batteries					
Typical backup times for 50 and 70% load*					
Evolution S	20/14 mn	14/9 mn	17/11 mn	15/10 mn	
Evolution S + 1 EXB	105/60 mn	60/36 mn	85/55 mn	60/42 mn	
Evolution S + 4 EXB	300/200 mn	180/115 mn	290/200 mn	210/135 mn	
Battery management	Automatic weekly test (period adjustable), automatic recognition of external battery units => continuous maximisation of backup time + deep discharge protection				
Interfaces					
Communication ports	1 USB port + 1 RS232 serial port and relay contacts (USB and RS232 ports cannot be used simultaneously) + 1 mini terminal block for remote ON/OFF and Remote Power Off				
Communications card slots	1 slot for NMC Minislot card (included in Netpack versions) or NMC ModBus/JBus or MC Contacts/Serial				
Operating conditions, standards and approvals					
Operating temperature	0 to 40°C				
Noise Level	< 45 dBA	< 45 dBA	< 50 dBA	< 50 dBA	
Performance - Safety - EMC	IEC/EN 62040-1-1 (Safety), IEC/EN 62040-2 EN 50091-2 class B (EMC), IEC/EN 62040-3 (Performance), IEC/EN 61000-4-2, 61000-4-3, 61000-4-4; 61000-4-5, 61000-4-6, 61000-4-8 (EMI)				
Approvals	CE, CB report, TÜV				
Dimensions W x H x D / Weight					
Dimensions	440 x 509 x 86.2 (2U) mm	440 x 509 x 86.2 (2U) mm	440 x 634 x 86.2 (RT2U) mm 440 x 484 x 130.7 (RT3U) mm	440 x 634 x 86.2 (RT2U) mm 440 x 484 x 130.7 (RT3U) mm	
Weight of the Tower/Rack	24.3 kg	26.6 kg	33.8 kg	33.8 kg (RT2U) - 34.3 kg (RT3U)	
Dimensions of EXB	See UPS				
Weight of the EXB	30.4 kg	30.4 kg	41.7 kg	41.7 kg	
Customer Service & Support					
2 years warranty	Standard product exchange, including the battery				
Warranty+	Optional 3-years warranty (depending on the country please visit www.eaton.com/powerquality)				
* Runtimes are shown at 0.7 power factor. Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.					
Part Numbers					
	S 1250 RT2U	S 1750 RT2U	S 2500 RT2U Netpack*	S 3000 RT3U	S 3000 RT2U Netpack*
Convertible Tower/Rack	68 456	68 459	68 463	68 464	68 465
EXB Models	68 470	68 470	2U = 68 472 - 3U = 68 471	2U = 68 472 - 3U = 68 471	2U = 68 472 - 3U = 68 471

* NMC card included in Netpack versions.

