

**POWER PROTECTION**

**OFFICE**

The Office range of filtered protected outlets provide surge and transient suppression for computer and office related equipment resulting from mains borne noise and induced lightning.

Available in different plug and socket standards, these units have an integral EMI/RFI filter, heavy duty surge arrester, thermal circuit breaker and fault indicator. Failsafe protection is provided by the inclusion of new "thermo-trip" technology.



- Slimline design
- Effective filter system
- Integral circuit breaker
- Fault indication
- Thermal disconnect protection

**TECHNICAL SPECIFICATIONS**

Max. continuous voltage	275V / 50Hz
Max. continuous current	15A
Earth leakage	< 1.5mA
Max. discharge current (8/20)	8kA
Residual voltage at 5kA (8/20)	Approx. 900V
Response time	< 25ns
Temperature range	-20°C to + 70°C
Standards compliance	IEC 99.4, IEC 950, IEC 61643-1

**ORDER CODES**

	<b>U.K.</b>	<b>GERMANY</b>	<b>S.A.</b>
5 way	12-00038	12-00146	12-00608
1 way	12-00201	12-00144	12-00696

We reserve the right to change specifications without prior notice

Cat/office

Tel: (011) 886- 7874

Fax: (011) 787-0178

Email: sales@sinetech.co.za