

POWER PROTECTION

RACKPOWER 2000 & RACKSTRIP 2000

A power strip with surge protection for communication and modem racks. Utilises a "2U" slot on a 483mm (19 inch) rack system and provides six socket outlets to power equipment. Various socket options are available. The Rackpower 2000 automatically disconnects the power to the equipment in the case of damage to the protection element or power overload. An integral On/Off switch with circuit breaker and indicator has been provided. EMI/RFI filtration is included. The Rackpower 2000 mounts horizontally while the Rackstrip 2000 is intended for side mounting and can accommodate up to 15 socket outlets, or a combination of power and data modules.

- Compact design
- Surge protection and filtration
- Failsafe protection
- Various socket combinations
-



TECHNICAL SPECIFICATIONS

Max. continuous voltage		275V / 50Hz
Max. continuous current		15 kA
Earth leakage		< 1.5mA
Max. discharge current (8/20)		8 kA
Response time		< 25ns
Filtration at 100kHz		50dB
Temperature range		10°C to + 70°C
Standards compliance		IEC 99.4, IEC 950, IEC 61643-1
Dimensions	Rackpower 2000	490 x 60 x 65 mm
	Rackstrip 2000	1000 x 40 x 65 mm

ORDER CODE

SOCKET	U.K.	GERMANY	S.A.
Rackpower 2000	12-00844	12-00842	12-00841
Rackstrip 2000	12-00849	12-00847	12-00846

We reserve the right to change specifications without prior notice

Cat/rackpower2000

Tel: (011) 886-7874

Fax: (011) 787-0178

Email: sales@sinetech.co.za