



# Parallel Switchmode Inverter

## Parallel Switchmode Inverter

RDI 3000VA - 110VDC – 230VAC

This new family of design-improved modular inverters can be supplied from any DC source in voltage range from 88 up to 160 VDC, providing pure sine wave output.

Several inverters can be connected in parallel to achieve the requested total power, including redundancy for best availability. Thanks to the full DSP control, true redundancy is achieved, while all informations are available both locally and remotely with SYS3000 controller and PSM2000 software.

The high frequency conversion and the topology used allow to reach very high efficiency in a compact and user-friendly design. The environmentally friendly range complies with International, European and general Industry standards.



### General features

- 2U up to 16 units in parallel
- High efficiency
- Full Digital Signal Processing control
- Outstanding response time
- Input/Output Radio Frequency Interference compliant to FCC
- Complete Supervision possibility
- Parallel operation in True Redundant System
- Large DC input voltage range
- Patented technology

## TECHNICAL SPECIFICATIONS

MODEL		120VAC	230VAC
Input	Operating voltage range	88 up to 160 Vdc	
	Maximum Input current	< 41 A	< 37 A
Output Specifications	Nominal output voltage	120V,adjustable 108...125Vac	230V,adjustable 200...240Vac
	Output voltage tolerance	+ 3% of adjustable nominal voltage	
	Output voltage frequency	50Hz or 60Hz, selectable	
	Total harmonic distortion	≤ 3% (on linear load at nominal power)	
	Total transient recovery time	≤ 0,3 msec (typical)	
	Turn-on-delay	< 3 sec.	
	Nominal value of output current	25 A	13 A
	Crest factor at nominal power	3	
Output Power	Nominal value	3000 VA	3000 VA
	Overload ( +/- 15%, 5 sec. Max, Self protected)	6000 VA	6000 VA
	Permanent overload	120 %	120 %
	Power factor, for 100% power	0 inductive to 0 capacitive Full 4 quadrants operation	
Electro-magnetic compatibility	Standards applied for immunity	EN 61000 – 4-2 / 4-3 / 4-4 / 4-5 / 4-6	
	Standards applied for emission	ETS300-132-2 CISPR 22 Class B	
Efficiency		87 %	89 %
Temperature	Storage temperature	- 40°C to 80°C	
	Permissible ambient temperature	- 20°C to 50°C	
Safety		EN60950 / UL1950	
Protections		Internal electronic + Relays + Fuses	
Dielectric Strength		4000VDC Input / Output      4000VDC Output / Earth 2000VDC Input / Earth	
Cooling		Forced	
Dimensions (W x D x H, mm)		438 x 348 x 2U	
Weight (Kgs, approximately)		14	

Sinetech reserves the right to change specifications without prior notice

Ref : cat2004/ RDI 3000-110

Tel: (011) 886-7874

Fax:(011) 787-0178

Email: sales@sinetech.co.za